

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/718,751	11/21/2003	Ayumu Ikemoto	062829	1834
38834 759 WESTERMAN, I	04/13/200 HATTORI, DANIEL	EXAMINER		
1250 CONNECT	ICUT AVENUE, NV	BRUENJES, CHRISTOPHER P		
SUITE 700 WASHINGTON, DC 20036			ART UNIT	PAPER NUMBER
Whomito i or ,	20030		1772	
			•	
SHORTENED STATUTORY F	PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE	
3 MONTHS		04/13/2007	PAPER	

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

	Application No.	Applicant(s)				
		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \				
Office Action Summary	10/718,751	IKEMOTO, AYUMU				
Office Action Summary	Examiner	Art Unit				
The MAILING DATE of this communication ap	Christopher P. Bruenjes	1772				
Period for Reply	pears on the cover sheet with the	correspondence address				
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING D. - Extensions of time may be available under the provisions of 37 CFR 1. after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period Failure to reply within the set or extended period for reply will, by statut Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATION 136(a). In no event, however, may a reply be will apply and will expire SIX (6) MONTHS from the course the application to become ABANDON	ON. timely filed om the mailing date of this communication. NED (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed on 09 J	lanuary 2007.					
	, 					
closed in accordance with the practice under	Ex parte Quayle, 1935 C.D. 11,	453 O.G. 213.				
Disposition of Claims						
4) ⊠ Claim(s) <u>1 and 3-8</u> is/are pending in the application 4a) Of the above claim(s) <u>8</u> is/are withdrawn from 5) □ Claim(s) is/are allowed. 6) ⊠ Claim(s) <u>1 and 3-7</u> is/are rejected. 7) □ Claim(s) is/are objected to. 8) □ Claim(s) are subject to restriction and/or	rom consideration.					
Application Papers						
9) The specification is objected to by the Examine	er.					
10) The drawing(s) filed on is/are: a) acc	cepted or b) objected to by the	e Examiner.				
Applicant may not request that any objection to the	= : :					
Replacement drawing sheet(s) including the correct						
11)☐ The oath or declaration is objected to by the E	xaminer. Note the attached Office	ce Action or form P1O-152.				
Priority under 35 U.S.C. § 119						
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of: 1. Certified copies of the priority documen 2. Certified copies of the priority documen 3. Copies of the certified copies of the priority documen application from the International Burea * See the attached detailed Office action for a list	ts have been received. ts have been received in Applica prity documents have been recei uu (PCT Rule 17.2(a)).	ation No ved in this National Stage				
Attachment(s)	•					
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date 20060913,20061130.	4) Interview Summa Paper No(s)/Mail 5) Notice of Informa 6) Other:					

Art Unit: 1772

DETAILED ACTION

Page 2

WITHDRAWN REJECTIONS

- 1. The claim objections of claims 3 and 4 of record in the Office Action mailed June 13, 2006, Page 2 Paragraph 2, have been withdrawn due to Applicant's amendments in the Paper filed January 9, 2007.
- 2. The 35 U.S.C. 102 rejection of claim 1 of record in the Office Action mailed June 13, 2006, Page 3 Paragraph 4, have been withdrawn due to Applicant's amendments in the Paper filed January 9, 2007.
- 3. The 35 U.S.C. 103 rejections of claims 2 and 3 over Enomoto in view of Poxon of record in the Office Action mailed June 13, 2006, Pages 4-6 Paragraph 7, have been withdrawn due to Applicant's amendments in the Paper filed January 9, 2007.
- 4. The 35 U.S.C. 103 rejection of claim 4 over Enomoto in view of Poxon and Ikeda of record in the Office Action mailed June 13, 2006, Pages 6-7 Paragraph 8, have been withdrawn due to Applicant's amendments in the Paper filed January 9, 2007.

Art Unit: 1772

- 5. The 35 U.S.C. 103 rejections of claims 5 and 7 over Enomoto in view of Poxon, Ikeda, and Kubota of record in the Office Action mailed June 13, 2006, Pages 7-9 Paragraph 9, have been withdrawn due to Applicant's amendments in the Paper filed January 9, 2007.
- 6. The 35 U.S.C. 103 rejection of claim 6 over Enomoto in view of Poxon, Ikeda, Ozawa, and Watanabe of record in the Office Action mailed June 13, 2006, Pages 9-12 Paragraph 10, have been withdrawn due to Applicant's amendments in the Paper filed January 9, 2007.

Election/Restrictions

7. Newly submitted claim 8 is directed to an invention that is independent or distinct from the invention originally claimed for the following reasons:

The original claimed invention and the invention of claim 8 are related as process of making and product made. The inventions are distinct if either or both of the following can be shown: (1) that the process as claimed can be used to make another and materially different product or (2) that the product as claimed can be made by another and materially different process (MPEP § 806.05(f)). In the instant case the product as

Application/Control Number: 10/718,751 Page 4

Art Unit: 1772

claimed can be made by another and materially different process such as applying a solvent to the rubber composition to render it flowable into the channels disposed between the rings of the metal bellows tube rather than heating the rubber to a flowable temperature.

Since applicant has received an action on the merits for the originally presented invention, this invention has been constructively elected by original presentation for prosecution on the merits. Accordingly, claim 8 is withdrawn from consideration as being directed to a non-elected invention. See 37 CFR 1.142(b) and MPEP § 821.03.

Claim Rejections - 35 USC § 103

- 8. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 9. The factual inquiries set forth in *Graham* v. *John Deere*Co., 383 U.S. 1, 148 USPQ 459 (1966), that are applied for

Art Unit: 1772

establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:

- Determining the scope and contents of the prior art.
- 2. Ascertaining the differences between the prior art and the claims at issue.
- 3. Resolving the level of ordinary skill in the pertinent
- 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.
- 10. Claims 1 and 3 are rejected under 35 U.S.C. 103(a) as being unpatentable over Doane et al (USPN 2,449,369) in view of Rademacher et al (US 2004/0242780 Al).

Doane et al anticipate a flexible hose comprising a metal bellows tube (reference number 3, Figure 1 and col.3, 1.27-28) having a first rubber layer (reference number 7, Figure 1 and col.3, 1.28-36) on the outer circumference thereof. A reinforcing layer is formed on the exterior surface of the first rubber layer (reference number 4, Figure 1 and col.3, 1.50-55). An exterior layer is formed on the outer circumference of the reinforcing layer (reference number 5, Figure 1 and col.3, 1.57-63). The metal bellows tube has a corrugated structure with a plurality of spaced apart rings having peaks and a plurality of channels disposed between the rings forming valleys below the peaks (Figure 1). The width of the rings vary in a radial direction so that the width between peaks is narrower than the width of each valley below the peaks (Figures 1 and 2). It

would be obvious to one having ordinary skill in the art that the exact width of each channel between peaks would be determined based on the intended end result and size of the hose. The first rubber layer is of a rubber composition that is flowable at low temperature such that each channel is filled with rubber extending throughout each valley (Figure 1).

Although Doane et al teach the rubber is a rubber cement, Doane et al fail to teach the specific rubber used in forming the rubber cement. However, Rademacher et al teach that it is preferred to form rubber cement from EPDM (p.2, paragraph 19) and that the EPDM is combined with acrylic rubber depending on the desired end properties for the rubber (p.2, paragraph 21). Because the rubber cement is formed to flow into the channels formed by the metal bellows and is formed of EPDM combined with acrylic rubber as claimed, the Mooney viscosity is obviously between 15 and 45 at 100°C because the rubbers having substantially the same composition should possess the same properties. Therefore, it would have been obvious to one having ordinary skill in the art at the time Applicant's invention was made to select EPDM combined with acrylic rubber as the rubber used in forming rubber cement because EPDM is a preferred rubber for that purpose as taught by Rademacher et al.

Art Unit: 1772

Thus, it would have been obvious to one having ordinary skill in the art at the time Applicant's invention was made to select the EPDM combined with acrylic rubber of Rademacher et al as the rubber for forming the rubber cement of Doane et al, since Doane et al only teaches rubber cement generally and Rademacher et al teaches that EPDM is a preferred rubber for forming rubber cement.

11. Claim 4 is rejected under 35 U.S.C. 103(a) as being unpatentable over Doane et al in view of Rademacher et al as applied to claim 1 above, and further in view of Ikeda et al (US 2002/0074050 A1).

Doane et al and Rademacher et al taken as a whole teach all that is claimed in claim 1 as presented above, but fail to teach that the intermediate rubber layer further comprises a resorcinol group. However, Ikeda et al teach a hose formed of metal bellows (p.6, paragraph 80) with a rubber layer bonded to the metal layer (p.5, paragraph 79). Ikeda et al further teach that a resorcinol group is added to a rubber bonded to an inner metal tube because the resorcinol group acts as an adhesive to the metal and improves adhesion between the metal and rubber (p.1, paragraph 14). Therefore, it would have been obvious to one having ordinary skill in the art that a resorcinol group is

added to a rubber layer that is bonded to a metal tube in order to improve the adhesion between the rubber and metal tube, as taught by Ikeda et al.

Thus, it would have been obvious to one having ordinary skill in the art at the time Applicant's invention was made that a resorcinol group would be added to the first rubber layer of Doane et al in order to improve the adhesion between the first rubber layer and the metal, as taught by Ikeda et al, since it is the desire of Doane et al to have a strong bond between the rubber and metal bellows.

12. Claims 5 and 7 are rejected under 35 U.S.C. 103(a) as being unpatentable over Doane et al in view of Rademacher et al and Ikeda et al as applied to claim 4 above, and further in view of Kubota et al (WO 2001/57132 A1). Note US 6,689,843 is the English equivalent of WO 2001/57132 A1 and the column and line citing will be from the US patent.

Doane et al, Rademacher et al, and Ikeda et al taken as a whole teach all that is claimed in claim 4 as presented above, but fail to teach that the first rubber layer comprising the acryl group is an acryl group of the formula claimed. The rubber composition claimed in claim 5 is an ethylene acrylic ester copolymer or ethylene acrylic rubber having a carboxyl

Page 9

Art Unit: 1772

'group. Rademacher et al teach that the rubber composition of the first rubber layer is formed of acrylic rubber, but does not explicitly teach that the acrylic rubber is an ethylene acrylic rubber further containing a carboxyl group or the percentage of ethylene, acrylic ester, and carboxyl groups present in the composition. However, Kubota et al teach that acrylic rubbers are widely used in the automobile field such as the hose of Doane et al because of its good heat resistance (col.1, 1.22-Kubota et al further teach that there is a demand for producing an acrylic rubber having more enhanced heat resistance (col.1, 1.24-26) and that adding a carboxyl group to the acrylic rubber increases the heat resistance (col.1, 1.65-67). Kubota et al teach that the acrylic rubber is formed of ethylene and acrylic acid ester monomers (col.3, 1.34-50). Kubota et al also teach that the acrylic acid ester monomer combined with the carboxyl group is contained in the mixture in an amount of 70% or greater (col.3, 1.50-55), which correlates to the combined value of y and z in claims 5 and 7. Kubota et al also teach that of the combination of acrylic acid ester and carboxyl group, the acrylic acid ester forms 90% or greater of the Therefore, Kubota et al teach values for x representing the ethylene monomer, y representing the acrylic ester portion, and z representing the carboxyl group that fall

Page 10

Application/Control Number: 10/718,751

Art Unit: 1772

within the ranges claimed in claims 5 and 7. Kubota et al teach that these values are determined because if the concentration of the ethylene monomer is too large the rubber becomes poor in rubber characteristics (col.3, 1.54-60) and if the concentration of the carboxylic group is too small the rubber is poor in crosslinkability and if it is too large the rubber has poor tensile strength and elongation (col.4, 1.1-9). One of ordinary skill in the art would have recognized that a carboxyl group is added to an ethylene acrylic acid ester co-polymer rubber in order to provide the rubber with enhanced crosslinkability and ultimately heat resistance, as taught by Kubota et al.

Thus, it would have been obvious to one having ordinary skill in the art at the time Applicant's invention was made to add a carboxyl group to the acrylic rubber of Doane et al and Rademacher et al in order to provide the rubber with enhanced heat resistance, which is an increasing demand in the automobile field, as taught by Kubota et al. Furthermore, it would have been obvious to one having ordinary skill in the art at the time Applicant's invention was made to set the relative amounts of the ethylene monomer, acrylic acid ester monomer, and carboxyl group would fall within the claimed range in order to form a rubber composition that has the desired amount of rubber

characteristics crosslinkability and tensile strength and elongation, as taught by Kubota et al.

13. Claim 6 is rejected under 35 U.S.C. 103(a) as being unpatentable over Doane et al in view of Rademacher et al and Ikeda et al as applied to claim 4 above, and further in view of Ozawa et al (USPN 6,492,454) and Watanabe et al (USPN 6,166,143).

Enomoto et al, Poxon et al, and Ikeda et al taken as a whole teach all that is claimed in claim 4 as presented above, but fail to teach that the first rubber layer comprising the acryl group is an acryl group of the formula claimed. The rubber composition claimed in claim 6 is an ethylene acrylic ester copolymer or ethylene acrylic rubber having an epoxy group. Rademacher et al teach that the rubber composition of the first rubber layer is formed of acrylic rubber, but does not explicitly teach that the acrylic rubber is and ethylene acrylic rubber further containing an epoxy group or the percentage of ethylene, acrylic ester, and epoxy groups present in the composition. However, Ozawa et al teach that in production of hoses comprising metal and rubber layers ethylene acrylic rubber or ethylene acrylic acid ester copolymer rubber is known to have excellent heat resistance but does not bond well to metal

(col.2, 1.40-53). Ozawa et al further teach that if ethylene acrylic acid ester is formed with an epoxy group such as ethylene-acrylic acid ester-glycidyl methacrylate copolymer rubber, the rubber does not require an additional polymer having epoxy groups to provide adhesiveness with a metal layer, because the epoxy group contained within the acrylic polymer provides the adhesiveness (col.11, 1.37-50). Therefore, it would have been obvious to one having ordinary skill in the art at the time Applicant's invention was made to select an ethylene acrylic rubber containing epoxy groups such as the ethylene-acrylic acid ester-glycidyl methacrylate copolymer rubber taught by Ozawa et al in order to provide the ethylene acrylic rubber with the ability to be adhere to the metal, as taught by Ozawa et al.

Thus, it would have been obvious to one having ordinary skill in the art at the time Applicant's invention was made to form the first rubber layer formed of acrylic rubber of Doane et al and Rademacher et al with an epoxy group, in order to provide the ethylene acrylic rubber with adhesiveness to the metal layer in the hose of Doane et al, as taught by Ozawa et al.

Ozawa et al fail to teach the individual percentages of the ethylene monomer, acrylic acid ester monomer, and epoxy group present in the first rubber layer. However, Ozawa et al does teach that the ethylene acrylic acid ester copolymer rubber has

Art Unit: 1772

any compositional proportion within the range generally used so long as the ethylene content therein is within the range that does not impair rubber elasticity and satisfy the characteristic of heat resistance (col.9, 1.64 - col.10, 1.4). Watanabe et al teach that the compositional proportions of the ethylene and acrylic ester is between 50:50 and 85:15 in order to maintain rubber elasticity (col.4, 1.40-50). Watanabe et al also teach that the epoxy group is found in the copolymer rubber in an amount between 0.05 and 5mol%. Therefore, Watanabe et al teach values for x representing the ethylene monomer, y representing the acrylic ester portion, and z representing the epoxy group that fall within the ranges claimed. Therefore, it would have been obvious to one having ordinary skill in the art at the time Applicant's invention was made that the compositional proportions taught by Watanabe et al are within the range generally used because the proportions are used in order to maintain rubber elasticity of the rubber, as taught by Watanabe et al.

Thus, it would have been obvious to one having ordinary skill in the art at the time Applicant's invention was made to select the compositional proportions of the ethylene monomer, acrylic acid ester monomer and epoxy group of the first rubber layer of Doane et al, Rademacher et al, and Ozawa et al within

the claimed ranges, since Ozawa et al teach that the compositional proportions fall within the range generally used in order to preserve the rubber elasticity of the composition and Watanabe et al teach specific values within the claimed ranges as the proportions required to ensure that the composition maintains its rubber elasticity.

Response to Arguments

14. Applicant's arguments with respect to claims 1 and 3-7 have been considered but are moot in view of the new ground(s) of rejection.

Conclusion

15. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, THIS ACTION IS MADE FINAL. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened

Page 15

Application/Control Number: 10/718,751

Art Unit: 1772

statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Christopher P. Bruenjes whose telephone number is 571-272-1489. The examiner can normally be reached on Monday thru Friday from 8:00am-4:30pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Harold Pyon can be reached on 571-272-1498. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Application/Control Number: 10/718,751 Page 16

Art Unit: 1772

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Christopher P Bruenjes Examiner

Art Unit 1772

CDD CPB

April 5, 2007

ALICIA CHEVALIER